

The Latest Abadan Light Naphtha Guaranteed Specification

TEST	UNIT	LIMIT	Test Method
Density @ 15.0 C	Kg/m3	700	ASTM D1298
Distillation	°C		ASTM D86
IBP	°C	35	ASTM D86
10% Evaporated Temp	°C	60	ASTM D86
50% Evaporated Temp	°C	85	ASTM D86
95% Evaporated Temp	°C	125	ASTM D86
FBP	°C	150	ASTM D86
Residue	% Vol	1.5	ASTM D86
Loss	%Vol	1	ASTM D86
Total Sulphur	% Wt	0.03	ASTM D1266
Corrosion 3 HRS	50°C	No 1 strip	ASTM D130
Vapour Pressure	K.Pa	75	ASTM D32
Mercaphtan Content	ppm	25	ASTM D322
Colour, Saybolt		20	ASTM D156
Paraffins Content	%Vol	70	ASTM D1319
Oleffins Content	%Vol	2	ASTM D131
Naphthenes Content	%VOL	10	ASTM D131
Aromatics Content	%VOL	5	ASTM D131
Lead (PB) P.P.B	UOP	40	350-68T
C/H Ratio	Estimated	5.5	Calculate
Gum Existent (air jet)	Mg/100ml	3	ASTM D381