

**FOROZAN ECRUDE OIL**

TEST	UNIT	LIMIT	Test Method
Specific Gravity @ 15.56/15.56 °C		0.8738	ASTM D5002
API Gravity	API	30.4	ASTM D5002
Sulfur Content (Total)	wt.%	2.21	ASTM D4294
H <sub>2</sub> S Content	ppm	51	IP 570
Mercaptan Content	ppm	79	UOP 163
Nitrogen Content (Total)	wt.%	0.13	ASTM D 5762
Water & Sediment	vol.%	0.15	ASTM D4007
Water Content	vol.%	0.1	ASTM D4006
Salt Content	PTB	22	ASTM D3230
Kinematic Viscosity @ 10 °C	mm <sup>2</sup> /s	24.10	ASTM D445
Kinematic Viscosity @ 20 °C	mm <sup>2</sup> /s	16.47	ASTM D445
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	6.159	ASTM D445
Pour Point (Upper)	°C	21	ASTM D5853
Reid Vapor Pressure	psi	5.30	ASTM D323
Asphaltene Content	wt.%	3.0	IP 143
Wax Content	wt.%	5.3	BP 237
Drop Melting Point of Wax	°C	57	IP 133
Conradson Carbon Residue	wt.%	6.00	ASTM D189
Total Acid Number	mg KOH/g	0.42	UOP 565
Nickel Content	mg/kg	12	ASTM D5863
Vanadium Content	mg/kg	36	ASTM D5863
Iron Content	mg/kg	1	ASTM D5863
Lead Content	mg/kg	<1	ASTM D5863
Sodium Content	mg/kg	50	ASTM D5863
Zinc Content	mg/kg	<1	ASTM D5863
Copper Content	mg/kg	<1	ASTM D5863